Miles 80.—No. 10 B.W.G. double-galvanized telephone steel wire, conforming to latest British Standard Specification; to be supplied in 1 cwt. coils.

Note.—Tenderers should furnish the following details:—

(1) Weight per mile.
(2) Resistance per mile at 20°C.
(3) Ultimate strength.

The supply on this tender would be subject to the conditions of contract obtaining in this department for local purchases.

Failure to supply the wire within the agreed time will entail not only cancellation of the order but also the purchase being made at the cost of the firm failing to fulfil the contract.

The Chief Electrical Engineer will not bind himself to accept the lowest tender or to assign any reason for accepting tender of any firm other than the lowest. His decision in all cases of dispute in respect of this tender will be final.

M. HAYATH,
For *Chief Electrical Engineer.*

OFFICE OF THE SUPERINTENDENT, POWER AND LIGHTING, MYSORE.

Notification dated 16th February 1940.

1. Sealed tenders in triplicate will be received at the Office of the Superintendent, Power the Lighting, Mysore, superscribed with the name of the work noted below.

2. A sum of Rs. 95 (Rupees Ninety-five) only is required to be sent along with the tender in cash or currency or cheque drawn in favour of the Superintendent, Power and Lighting, Mysore or order, being the earnest deposit. *Tenders not accompanied with the said deposit will not be accepted.*

3. The plans connected with the work may be seen at the office of the undersigned at all working hours. The same will be made available on payment of Rs. 3 per set, if required.

4. The tender should be drawn up strictly in conformity to the specifications furnished writing out the rates at which each item of work will be executed in figures as well as in words, failing which, no cognizance will be taken of the tender. *The type of wiring adopted being in conduit embedded in the wall it has been arranged to cut open the Grooves for laying the conduit including the niche, to plaster and finish the surface damaged, through the agency of the Public Works Department. The tender should comprise provision exclusively for the electrical portion of the work.* No items other than those incorporated in the statement should be included in the tender as the items cover provision for all the necessities to the satisfactory execution of work.

5. Materials to be used on the work should be of best quality conforming to the specification of this department and B.S. or A.I.E.E. Specifications. Mention should also be made of the manufacture and the catalogue numbers of the materials offered. Teakwood planks to be used on the work should be free from knots, cracks and should be well seasoned. No plank less than 12″ in width will be permitted to be used unless it is to make up the difference in size of the board required. Only lap joints should be adopted in all cases.

6. The undersigned reserves the right to reject the tenders without assigning any reason therefor.

7. The successful tenderer will be required to execute an agreement within two days from the date of communication of acceptance of the tender. He should arrange to send for inspection the materials to be employed on the work and start the work after obtaining the approval of the undersigned with regard to the same within a week from the date of communication of acceptance. Failure to adhere to the conditions above will entail forfeiture of the earnest deposit and adoption of such measures as are necessary for expediting completion of the work otherwise entirely at his risk. He should also bind himself to execute the work strictly adhering to the wiring rules of this department as well as those of I.E.E. He should also be prepared to adopt changes in the location of lighting fixtures control points, etc., that might be desired by the undersigned during the progress of the work without any obligation if the tender is not materially affected thereby. It may be noted that the control switches of the lighting outlet as also wall plugs should be grouped and located at a height between 2½ to 4 feet above floor level as per directions at the time of the execution.

8. The undersigned reserves the right to reject the work either in full or in part if the same is not executed according to the above specifications or is not satisfactory as regards workmanship.

9. Special care should be taken to afford metallic continuity and to provide efficient earthing to the installation as the system of wiring adopted is in conduit.

10. *Name of work.*—Installing electric lights and heating circuits to the Special Ward of 12 beds at Krishnarajendra Hospital, Mysore.

11. *Last date and time of receiving the tender.*—At 3 P.M. on the 11th March 1940.

12. *Last date and time for opening the tender in public.*—At 4 P.M. on 11th March 1940.

13. A period of 8 weeks from the date of acceptance of tender will be allowed for the completion of work in all respects. If the installation is not handed over to the department with service on the due date, the department will arrange to take charge of the installation at whatever stage it might be and arrange for completion of the work through any other agency at the risk of the tenderer.

14. The firm executing the work should arrange while handing over the installation to this Department to pass a certificate of guarantee for the continuance of satisfactory service to the installation for a period of 12 calendar months from the date of handing over charge to this Department while uninterrupted power supply is maintained. Further, it will be obligatory on the part of the Firm to attend to any defects in the installation that might crop up during the above period without any return for service rendered.

15. *Details of work.*—The quantities given in the annexed Statement are not guaranteed and are subject to variation at the time of executing the work.

Installing Electric lighting and heating circuits to the Special Ward of 12 Beds at Krishnarajendra Hospital, Mysore.

Sl. No.	Particulars	Unit	Quantity
	Part I—Mains.		
1	Supplying and laying No. 7/.036 SWG. twin core paper insulated, lead covered, double steel tape armoured, jute served, underground cable suitable for 1,000-Volts working pressure in a trench 3 feet deep, surrounding the same with 3" fine sand enclosing the ends of the cable in pole and indoor type C. I. junction boxes filled with insulating compound and the vertical run of the cable at the pole end in 18" of 1½" C. I. pipe with bends and clamps etc., using No. 7/.036 SWG. insulated wire and accessories (for lighting mains)	R.ft.	130
2	Do do 7/.064 SWG. twin core cable in the same trench as provided in item (1) above and as per specification above ..	„	130
3	Running mains in ¾" braized conduit embedded in the wall with necessary clamps and bends using No. 7/.036 SWG. insulated wire and accessories	„	4
4	Do do in 1" braized conduit as per specification above, using No. 7/.064 SWG. insulated wire and accessories ..	„	4
5	Supplying, fixing and wiring at W. board, 4'-6"×2'×1" with 2" battens and rear board enclosed in a box of compressed cement asbestos ⅜" thick mounted in a niche with panelled ground glass shutter, 6 lever Aligarh lock and key complete and equipped with (*a*) one 15 Amp. D.P.S.T. iron clad switch with fuse arrangement (for lighting main), (*b*) two 10 Amp. D. P. S. T. iron clad switches with fuse arrangements (for lighting Distribution) and (*c*) one 30 Amp. D. P. S. T. iron clad switch with fuse arrangement (for heating) using No. 7/.036 SWG. and 7/.064 SWG. insulated wire and accessories	No.	1
6	Earthing cable armouring metal clad switches, conduits, etc.	L. S.	
	Part II—Lighting outlets.		
1	Supplying, fixing and wiring for lighting outlets in ¾" heavy gauge welded conduit embeded in the wall with flush mounting junction boxes, bends, elbows, inspection boxes, etc., using 5 Amp. flush type control switch with plate cream finish using No. 7/.029 SWG. and 3/.036- SWG. insulated wire for mains and taps respectively and accessories ..	No.	7
2	Do do for ceiling fan and lighting outlets complete with suspension clamp, 3 plate bakelite C. R. cream finish hook T. W. Block for regulator 5 amp. control switch, etc., as above	„	2
3	Wall receptacles complete with five flush type wall plug with nipple controlled by 5 amp. flush type switch as above	„	8
	Part III—Heating.		
1	Supplying, fixing and wiring in 1" welded conduit for heating outlets, embeded in the wall complete with necessary flush type inspection boxes T's etc., and 15 amp. 230 volts, 3 pin interlocking type sockets and plugs, flush type complete with C. I. Box and protected by a pair of 15 Amp. fuses all mounted flush with the wall using 7/.064 SWG. insulated wire and accessories	No.	2
	Part IV—Lighting Fixtures.		
1	Supplying and fixing flange type B. C. lamp holders all nickel plated complete with 10"×5" green and white opal shade 60 watts, 230 volts, B. C. frosted lamps and accessories	„	5
2	Do do for brass pendents ⅝" 2 to 3 feet long holder, ceiling plan all nickel plated, complete with 10"×5" white opal shade, 60 watts, 230 volts B. C. frosted lamp and accessories	„	2
3	Do do ceiling fans 3 or 4 blades 56" sweep 60 cycles, 230 volts, 5 speeds and off position hollow spindle complete with 3 to 4 ft. down rod wall mounted regulator equipped with a lighting unit complete with 10" white opal round domes nickel plated metal gallery and 150 watts, 230 volts, B. C. lamp	„	2

Sl. No.	Particulars	Unit	Quantity
	Part V.		
1	Supplying one water boiler 20 gallon capacity non-pressure type with internal container, tinned copper of 2,000 watts capacity, 230 volts ..	No.	1
2	Erecting and wiring the above boiler with necessary accessories ..	Item	..
	N.B.—The manufacture of the boiler offered with clear specification should be noted.		

Notification dated 20th February 1940.

1. Sealed tenders in triplicate will be received at the Office of the Superintendent, Power and Lighting, Mysore, superscribed with the name of the work noted below.

2. A sum of Rs. 50 (Rupees Fifty) only is required to be sent along with the tender in cash or currency being the earnest deposit. Tenders not accompanied with the said deposit will not be accepted.

3. The plans connected with the work may be seen at the office of the undersigned at all working hours. The same will be made available on payment of Rs. 3 per set.

4. The tenders should be drawn up strictly in conformity with the specifications furnished writing out the rate at which each item of work will be executed in figures as well as in words, failing which no cognisance will be taken of the tender. No items other than those noted in the statement should be included, as the items cover provision for all sundries that are necessary for the execution of the work to meet with the requirements of the department including necessary repairs, painting the exterior of the casing to suit the colour wash.

5. Materials to be used on the work should be of best quality conforming to the specification of this Department and B.S. or A.I.E.E. specifications. Mention should also be made of the manufacture and the catalogue numbers of the materials offered. Teak wood planks to be used on the work should be free from knots, cracks and should be well seasoned. No planks less than 12″ in width will be permitted to be used unless it is to make up the difference in size of the board required. Only lap joints should be adopted in all cases.

6. The undersigned reserves the right to reject the tenders without assigning any reason therefor.

7. The successful tenderer will be required to execute an agreement within two days from the date of communication of acceptance of the tender. He should start the work after obtaining the approval for the materials to be employed on the work by the undersigned within a week from the date of communication of acceptance. Failure to adhere to the conditions above will entail forfeiture of the earnest deposit and adoption of such measures as are necessary for expediting the work otherwise entirely at his risk. He should also bind himself to execute the work strictly adhering to the wiring rules of this Department as well as those of I.E.E. He should also be prepared to adopt changes in the location of lighting fixtures, control points, etc., that might be desired by the undersigned during the progress of the work without any obligation, if the tender is not materially affected thereby. It should also be noted that control switches, wall plugs, etc., should be grouped wherever necessary and located as far as possible in inconspicuous places.

8. The undersigned reserves the right to reject the work either in full or in part if the same is not executed according to above specifications or is not satisfactory as regards workmanship.

9. *Name of work.*—Installing Electric lights to the 'A' Depot Store Keeper's Office and 'B' Stationery Depot at Central Stores, Mysore.

10. *Last date and time of receiving the tender.*—At 3 P.M. on 11th March 1940.

11. *Last date and time for opening the tender in public.*—4 P.M. on 11th March 1940.

12. A period of eight weeks from the date of acceptance of tender will be allowed for the completion of the work in all respects. If the installation is not handed over to the Department with service on the due date, the Department will arrange to take charge of the installation at whatever stage it might be and arrange for completion of the work through any other agency, at the risk of the tenderer.

13. The Firm executing the work should arrange while handing over the installation to this Department to pass a certificate of guarantee for the continuance of satisfactory service to the installation for a period of 12 calendar months from the date of handing over charge to this Department while uninterrupted power supply is maintained. Further, it will be obligatory on the part of the firm to attend to any defects in the installation that might crop up during the above period without any return for service rendered.

14. *Details of work.*—The quantities given in the annexed statement are not guaranteed and are subject to variation at the time of executing the work.

"A".

Installing electric lights to the Depot Store Keeper's Office, Railway Workshop, Mysore.

No.	Names of materials, etc.	Unit	Quantity
	Part I.		
1	Supplying, fixing and wiring single pole 30 Amps. iron clad service cut out on the board available in the verandah of the stores, using No. 7/.036 SWG. insulated wire and accessories	No.	2
2	Supplying and running mains in two-way 2″×1″ T. W. casing treated with two coats of shellac varnish using No. 7./036, SWG. insulated wire and accessories	R.ft.	140′
3	Supplying and laying No. 7/.036 SWG. twin conductor paper insulated, lead covered double steel tape armoured jute served, underground cable for 1,000 volts pressure, in a trench of 3 feet deep surrounding the same with 3″ of fine sand, enclosing the ends of the cable in two indoor type junction boxes filled with insulating compound and connecting the same with the sub-mains run in casing, using necessary length of 1½″ galvanized pipe for enclosing the cable running below the Railway line No. 7/.036 SWG. insulated wire with accessories	,,	70′
4	Earthing	L. S.	..
	Part II.		
1	Supplying, fixing and wiring a teak wood board varnished 15″×12″×1″ with batten and rear board equipping it with a D. P. S. T. 15 Amps. iron clad switch with fuses, one D. P. H. O. pattern 3-way 10 amps. per way iron-clad distribution box with 10 Amps. bakelite switches using No. 7/.036 and 3/.036 SWG. insulated wire and accessories	No.	1
2	Supplying, fixing and wiring in teak wood 2-way 2″×1″ casing treated with two coats of shellac varnish with capping for ⅝″ brass pendants 5 to 6 feet long complete with stout brass ceiling plated B. C. lamp holder (all nickel plated) 5 amps. bakelite control switches and No. 3/.036 SWG. insulated wire and accessories	,,	3
3	Do do for 1½″ to 2 feet long as per above specification	,,	2
4	Do do for O. C. bracket 6″×½″ as per above specification	,,	1
5	Do do for ceiling fans, A. C. 220 volts, 56″ sweep, 60 cycles complete with canopy, down rod 5 point variable speed regulator, providing underneath it an Ivanhoe Trojan fitting unit complete with B. C. lamp holder canopy, 12″ glass ware, etc., using 3 plate bakelite ceiling rose; flexible cord 5 Amp. bakelite control switches, etc., using No. 3/.036 SWG. insulated wire and accessories	,,	1
6	Do do for ceiling fan as per specification above but without lighting unit	,,	1
7	Supplying, fixing and wiring for ceiling fan and lighting outlets provided with an Ivanhoe Trojan lighting unit suspension type, complete with canopy, B. C. lamp holder chain, 12″ opal glassware, using 3-plate bakelite ceiling rose, etc., as per specification above ..	,,	2
8	Supplying and fixing shades, white opal 10″×5″	,,	4
9	Do shades, tin enamelled 10″×5″	,,	2
10	Do lamps, 60 watts, 220 volts, gas filled 'Mysore'	,,	6
11	Do lamps, 100 watts, 220 volts, gas filled 'Mysore'	,,	4

"B".

Installing Electric lights to the Stationery Depot at the Chief Store-Keeper's Office, Central Stores, Mysore.

	Part I.		
1	Supplying and running mains in 1″ W. I. pipe with bends, clamps, etc., using No. 7/.064 SWG. insulated wire and accessories ..	R.ft.	25′
2	Earthing	L. S.	..

No.	Names of materials, etc.	Unit	Quantity
	Part II.		
1	Supplying, fixing and wiring T. W. board 24″×18″×1″ with battened rear board equipping it with a 3-way distribution box (available in Chief Store-Keeper's Office) with circuit switches, one 15 amps. D. P. S. T. iron clad switch with fuses using No. 7/.036 SWG. insulated wire and accessories	No.	1
2	Do do in T. W. casing 2″×1″ treated with two coats of shellac varnish for drop lights complete with 2-plate bakelite ceiling rose, flexible cord, reinforced bakelite B. C. Lamp holder, 5 amperes control switch, with reinforced bakelite cover, etc., using No. 3/.036 SWG. insulated wire and accessories ..	,,	8
3	Do do ceiling fan A. C. 220 volts 56″ sweep, 60 cycles, complete with canopy down rod, 5 point variable regulator, etc., using 2-plate bakelite ceiling rose, clamps, etc., using No. 3/.036 SWG. insulated wire and accessoreis	,,	1
4	Do do for combined wall plug and switch with nipple 5 amperes as per specification above	,,	5
5	Supplying and fixing, white opal shades 10″×5″	,,	7
6	Do tin enamelled shades 10″×5″	,,	1
7	Do lamps, 60 watts, 220 volts, B. C. gas filled "Mysore"	,,	8

M. M. ALI KHAN,
Superintendent.

SRI NARASIMHARAJA HOSTEL, BANGALORE.

Notification No. 552, *dated 20th February* 1940.

Attention of the public is invited to the tender Notices published in pages 334 to 337, Part VI of the *Mysore Gazette*, dated the 15th February 1940, calling for the supply of provisions, curds and milk vegetables and stationery to the Sri Narasimharaja Hostel, Bangalore, for the year 1940-41.

M. S. RAJAGOPAL RAU,
President.

GOVERNMENT SANDALWOOD OIL FACTORY, MYSORE.

Abstract Notification.

The attention of the public is invited to the Notification " calling for tenders for the purchase of Old Cornish Boiler during 1939-40" published in pages 386-387, Part VI of the *Mysore Gazette* dated 22nd February 1940.

The last date of receiving tenders is fixed at 5 P.M. on the 15th March 1940.

S. G. SASTRY,
Director.

OFFICE OF THE MANAGER, BABBUR FARM, HIRIYUR.

Abstract Notification dated 17th February 1940.

The attention of the public is invited to the detailed notification dated 17th February 1940 calling for tenders for the purchase of jaggory manufactured on the Government Experimental Farm, Hiriyur, published on page 413, Part VI of the *Mysore Gazette*, dated 22nd February 1940.

The date fixed for the receipt of tenders is 11th March 1940.

ARCOT DEVARAJ,
Manager.